



 Explore and interact with products in 3D.
thelightexperience.iguzzini.com



- Framer
- Installation on Low Voltage track (48V) presented on page 272.
- Floodlight with DC / DC converter built into the adapter.
- Adapter-track connection with fast click-fit system.
- Floodlight body in die-cast aluminium.

- $\varnothing 19$ floodlight with metal gobo and manual focusing system
- $\varnothing 37$ floodlight with metal gobo and outer fins for adjusting and shaping the light beam.
- CoB LED with high colour yield index
- Compatible with Beacon accessory for 48V track



Compact dimensions



Magnetic system



Focusing



No stray light

Lighting effects - $\varnothing 19$

Circles with different dimensions can be adjusted using the internal metal gobo.
Manual focusing.





$\varnothing 19$ ($\varnothing 5mm$)		
m	\varnothing	lux
0,5	0,19	860
1	0,37	205
2	0,56	88
3	0,74	50





01
WHITE

04
BLACK

Lighting effects - ø 37



m	ø 37	
	L	lux
1	0,36	1606,79
2	0,72	401,70
3	1,08	178,53
4	1,44	100,42
5	1,80	64,27




m	ø 37 (ø=5)	
	ø	lux
1	0,17	1600,35
2	0,34	400,09
3	0,51	177,82
4	0,69	100,02
5	0,86	64,01



m	ø 37 (ø=10)	
	ø	lux
1	0,34	1684,14
2	0,68	421,03
3	1,02	187,13
4	1,36	105,26
5	1,70	67,37

Shape&Twist - ø 37

External wings for manual adjustment of shapes (three- and four-sided) - Shape



Precision adjustment by rotating the body without having to open the product - Twist!



iguzzini.com 🔍 code finder / 📄 download design files / ☆ save and organize favorites

new
available from July

source	system		code	colour
	W	lm		
LED				
4000K - CRI 90 - DALI				
• 2W	160	-	-	QX10 01-04
3000K - CRI 90 - DALI				
2W	180	3,4W	4	Q648 01-04
2700K - CRI 90 - DALI				
2W	170	3,4W	3	Q649 01-04



source	system		code	colour
	W	lm		
LED				
4000K - CRI 90 - DALI				
• 11W	920	-	-	QX11 01-04
• 11W	920	-	-	QX45 01-04
3000K - CRI 90 - DALI				
6,5W	620	8W	31	Q650 01-04
2700K - CRI 90 - DALI				
6,5W	590	8W	30	Q651 01-04
4000K - CRI 90 - DALI / Push Dim				
• 11W	920	-	-	QX44 01-04



Class III product performances are assured only when using the electronic power supplies and drivers indicated in the catalogue.

For missing watt and lumens values consult iguzzini.com - Technical information may change alongside technological progress. Consult iguzzini.com for ongoing updates.